



PLATFORM SIZE	A	B	C	D
36X48	36.25	48	31.81	7.13
36X54	36.25	54	31.81	7.13
36X60	36.25	60	31.81	13.13
42X60	42.25	60	34.81	13.13

Specifications
 Model: VP19
 Rated Load: 750 lbs
 Drive: Dual winding cable drums / 24 VDC
 500 watt motor w/brake
 Supply Power: 120 VAC 15A
 Operating Power: 24 VDC (DUAL 12V 10AH BATTERIES)
 Control Power: 5 VDC
 Platform: 36" x 48" (36" x 54")(36" x 60")(42" x 60")
 Lift Height: 1" - 144"
 Speed: 15-18 fpm
 Controls: Constant pressure paddle switch
 Safety Standards: ASME A18.1, Section 2
 CSA B44.1/ASME A17.5
 Safety Features: Safety pan, final limit, slack cable brake,
 emergency stop w/alarm

**DESIGNED TO COMPLY
 WITH ANSI A18.1 PART 2
 WHEN PROPERLY INSTALLED**

MODEL	X	Y
PLO-048	48	93.06
PLO-072	72	117.06
PLO-096	96	141.06
PLO-0120	120	165.06
PLO-0144	144	189.06

SHCA
STAYING HOME CORPORATION

Staying Home Corporation
 2501 Anaconda Rd
 Harrisonville, MO 64701
 816-380-2427
 www.stayinghome.com

TITLE: PLATFORM LIFT - OPEN

SIZE B	DWG. NO. TYP-PLO	REV
SCALE:	WEIGHT:	SHEET 1 OF 1

01/24/2019

2