



ALUMINUM AND ACRYLIC ENCLOSURE

DOUBLE 2X6 WITH 2X4 ON EACH SIDE-FLOOR TO CEILING AT EACH FLOOR
ANCHOR LOCATIONS

DETAIL A SCALE 1 : 4

Battery Powered: 24 VDC Control System
 Rated Load: 500 lbs
 Speed: 15 fpm
 Max. Travel: 21'-0"
 Winding Drum Drive with dual 1/4" aircraft cables
 Automatic up/down controls
 Key Lock on controls
 Emergency Stop Switch and Alarm
 Recessed Automatic LED Car Light
 Status LED Indicator
 Door Position switch on Sliding Car Door
 Slack Cable Safety Device with Switch
 Final Limit Switches

SECTION A-A
SCALE 1 : 16

SPECIFICATIONS AND DIMENSIONS
SUBJECT TO CHANGE WITHOUT NOTICE

DESIGNED TO COMPLY WITH ASME A17.1 PART 5.3 WHEN PROPERLY INSTALLED

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STAYING HOME CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STAYING HOME CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL ±1/16
 ANGULAR: ±0.5°
 ONE PLACE DECIMAL ±0.1
 TWO PLACE DECIMAL ±0.01
 THREE PLACE DECIMAL ±0.005
 INTERPRET GEOMETRIC TOLERANCING PER:
 MATERIAL:
 FINISH:
 DO NOT SCALE DRAWING

NAME	DATE
DRAWN	7/16/2019
CHECKED	
ENG APPR.	
MFG APPR.	
Q.A.	
PROJECT:	



Staying Home Corporation
 2501 Anaconda Rd
 Harrisonville, MO 64701
 816-380-2427
 www.stayinghome.com

TITLE:
EZ6 FRONT ENTRY, LH CAR DOOR INSIDE SHC ENCLOSURE

SIZE DWG. NO.
B TYP - EZ6F-A-LH REV

SCALE: 1:96 WEIGHT: SHEET 1 OF 1