



ALUMINUM AND ACRYLIC ENCLOSURE

DOUBLE 2X6 WITH 2X4 ON EACH SIDE-FLOOR TO CEILING AT EACH FLOOR

ANCHOR LOCATIONS

DETAIL A SCALE 1 : 4

CAR GATE RH SLIDE

- Battery Powered: 24 VDC Control System
- Rated Load: 500 lbs
- Speed: 15 fpm
- Max. Travel: 21'-0"
- Winding Drum Drive with dual 1/4" aircraft cables
- Automatic up/down controls
- Key Lock on controls
- Emergency Stop Switch and Alarm
- Recessed Automatic LED Car Light
- Status LED Indicator
- Door Position switch on Sliding Car Door
- Slack Cable Safety Device with Switch
- Final Limit Switches

DESIGNED TO COMPLY WITH ASME A17.1 PART 5.3 WHEN PROPERLY INSTALLED

SECTION A-A SCALE 1 : 16

SPECIFICATIONS AND DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STAYING HOME CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STAYING HOME CORPORATION IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN INCHES
 TOLERANCES:
 FRACTIONAL: ±1/16
 ANGULAR: ±0.5°
 ONE PLACE DECIMAL ±0.1
 TWO PLACE DECIMAL ±0.01
 THREE PLACE DECIMAL ±0.005

INTERPRET GEOMETRIC TOLERANCING PER:
 MATERIAL
 FINISH

DO NOT SCALE DRAWING

NAME	DATE
DRAWN	7/16/2019
CHECKED	
ENG APPR.	
MFG APPR.	
Q.A.	
PROJECT:	



Staying Home Corporation
 2501 Anaconda Rd
 Harrisonville, MO 64701
 816-380-2427
 www.stayinghome.com

TITLE: EZ6 FRONT ENTRY RH CAR DOOR INSIDE SHC ENCLOSURE	
SIZE: WG. NO.	REV
B TYP - EZ6F-A-RH	
SCALE: 1:96	WEIGHT: SHEET 1 OF 1